



## Maintenance Instructions -- RESILIENT TILE FLOORING -- EcoScore

### Endura EcoScore™ Multifunctional Athletic Flooring Maintenance Instructions

#### Introduction

To support our customers' maintenance programs, Endura recommends the use of Taski and Johnson Wax Professional cleaning products. Additional information and MSDS for the specific cleaning products contained herein may be obtained from JohnsonDiversey at 1-800-558-2332.

#### Post Installation Initial Cleaning

Initial cleaning should not be performed until seventy-two (72) hours after installation.

1. Thoroughly sweep or vacuum the flooring to remove all loose dirt and grit.
2. Prepare a cleaning solution of 2 to 4 oz of Taski "Profi" or Johnson Wax Professional "Stride" oil and grease emulsifying neutral detergents (pH of 7-8), per gallon of warm water. The dilution selected depends on light to heavy soil conditions.
3. Apply the cleaning solution with a nylon or rayon mop, and let stand for 5-15 minutes. **IMPORTANT: do not let the solution dry.**

4. Scrub the rubber floor tiles:

**Small area installations:** use a deck brush.

**Large area installations:** use a 22 gauge flagged nylon bristle brush on a single disk scrubbing machine with a maximum disk speed of 150-300 RPM.

5. Wet vacuum, or mop up, the cleaning solution.
6. Rinse with clean cold water, and then remove all water by vacuum or mop.
7. Allow the flooring to dry thoroughly. (Approximately one hour, depending on temperature and humidity).

**REGULAR MAINTENANCE**

Daily cleaning is recommended.

1. Sweep or vacuum the floor daily when area is in use.
2. Apply Taski "NDC" or Johnson Wax Professional "Triad II, Virex II, or Forward DC" disinfectant cleaners to the floor utilizing a rayon or nylon mop or auto scrubber. Dilute according to container instructions depending on the amount of soiling.
3. Allow the cleaner to stand for 10 minutes on the floor surface, then agitate with a deck brush or auto scrubber equipped with a 22 gauge flagged nylon bristle brush. Use an auto scrubber or single disk scrubbing machine with a maximum disk speed of 150-300 RPM.
4. Use a wet/dry vacuum to remove soiled solution from the floor. Rinsing the floor is not required.

**SPECIAL MAINTENANCE CAUTIONS**

1. Removing Gum -- Apply dry ice on the affected area and carefully remove the frozen gum with a non-metal spatula. Mineral spirits can be used to remove any remaining residue. Hand buff the spot with a soft towel.
2. Do not use scrubbing or buffing pads, steel wool, strong solvents (Lestoil, Top Job, etc. and similar products), gasoline, turpentine, and acetone.
3. Do not use mechanical polishers that exceed 350 RPM.