



Specification Data – ATHLETIC RESILIENT SHEET FLOORING 09 65 66

EcoFitness Sheet Rubber Flooring Specifications

COMPOSITION: Poly-bonded granular post consumer recycled black rubber or with EPDM Colored Rubber Flecks.

THICKNESS: Standard 3/8" (9.5mm) thickness available.

WIDTHS: Standard 4 feet.

LENGTHS: 25 Feet and 50 Feet Rolls.

COLORS: Solid Black, 17% color in Blue, Grey, Green and Mocha. Custom colors and percentages available with minimum 2,000 Square Foot purchase. Note; Custom color quantities must be in 2,000 foot increments.

TESTS BELOW ARE ON 3/8" (9.5 mm) THICKNESS MATERIAL:

ACOUSTIC RATING: Superior

CHEMICAL BEHAVIOR: Resistant to water, various diluted acids and alkaline solutions and UV resistant.

DENSITY: 60 lb/ft³ or 980 kg/m³

DUROMETER HARDNESS SHORE A: 55

ELONGATION: < 145 %

SHEARING STRENGTH: < 0.60 (N/mm²)

TEMPERATURE STABILITY: -30°C up + 80°C in resting conditions

TENSILE STRENGTH: < 1.80 (N/mm²)

TOLERANCES: Thickness +/- 3%, Width +/- 1%, Length +/- 1%

PRODUCT WEIGHTS

THICKNESS (mm) NOMINAL THICKNESS (in) AVE. WEIGHT

3/8" (9.5 mm) is 27.6 oz / ft²